



TASMANIAN OAK

Having long been prized as a floor covering in Australia, Tassie Oak is making a resurgence in popularity. Its straw shades and soft muted pinks perfectly fit the modern vogue for timbers with a lighter appearance. With its even colouring and grain structure, Tassie Oak is a must for anyone seeking a fresh, contemporary appeal.

Tasmanian Oak is the name used to describe a blend of three eucalypts commonly found in Tasmania. Blended together, they produce an extremely stable floor with tones ranging from pale brown and gold to faint pinks and light brown. The grain of Tasmanian Oak is straight and is open and coarse in nature. Tasmanian Oak is one of the most popular choices of flooring in today's market.

MECHANICAL VALUES

Available Sizes Collections
Dimensions Surface Wear Layers

PREMIUM COLLECTION: 14/3-14/4
x 136 mm/180 mm wide 1800/2200
mm

ENVIRO COLLECTION: 14/1.5 mm
-150 190 wide x 1900/2200 mm

Construction

Single strip all on cross laminated ply-wood

Surface Finishes

LACQUER: 9-14 coats system-
German Klumpp Treffert Aluminum
Ceramic Oxide with Harder Top Coats
- U.V. Cured

OIL: 8-10 coats system-Danish Oil
WOCA considered to be one of the
best in the world- U.V. Cured

Board Style

Square Edge/ Micro Bevel

Locking System

Tongue and Groove

Installation Methods

Glued down method-to concrete or
yellow tongue sub floors

Floating method- on an acoustic
water resistant membrane underlay

Internal Expansion

Allow an expansion joint of 10 mm for every 6 metres of flooring. Expansion joint caulked and/or covered with HAUS Hardwood T-mould or HAUS Aluminum T-mould

External Expansion

Allow an expansion joint to perimeter 10-15 mm from the wall and all internal joinery. Expansion joint to be caulked and/or covered with timber or skirting

Moisture Content

10-12%

Timber Hardness

JANKA 1350 LBF
NEWTON 6.0 N

AUSTRALIAN SPECIES GRADING

HAUS has graded our Engineered Timber as follows:

Lacquered / Oiled Boards 136/ 180/190mm 14/3- 14/4mm Select/ Standard & Better this means that you can expect the following:

- Features: Relatively Small to Medium in size with most boards having some character, all will be visible
- Gum Veins , Borer Holes, Gum Pockets, Burls, Insect Trails, some checking will occur (small surface cracks)
- Small Knots, can be expected, all these are character Features of the Australian Species and are not defects
- Wire Brushed collection: you can expect significantly more features and character throughout the range, with some peppering and larger Gum Veins and Checking.
- HAUS advises all their clients to research their Floor Purchase prior to installation by visiting a Showroom where they can see a larger section of Flooring on display, this will then help them in by understanding what they can expect from their Hardwood Timber Floors once installed.
- Engineered Hardwood Timber Floors are a Lifetime Investment that will add Value to your property, therefore we recommend that you spend time and research your Timber Floors before purchasing.



Unit 3 Number 4 Fortitude Crescent, BURLEIGH 4226 | AUSTRALIA-PHONE : 1300 725 257

Email: sales@haus.com.au www.haus.com.au ATFA member of the Australian Timber Flooring Association

ABN 86 625 623 529 ACN 103 979 531 QBCC Licence 1196468